


Tool Box – Multi Data Analysis


This function is similar to Sensor Data Diagnosis, which supports the analysis of each sensor item of multiple controllers mounted on the vehicle on a single screen at the same time.

* It only supports modules that support CAN communication protocol.



Sensor Data Item Selection

Select a sensor data item to analyze. Select items for each system to analyze.



Mode

This section describes the sensor data indicating mode.

Text Mode \equiv

It indicates sensor data in text format.



Bar Graph Mode 😑

It indicates sensor data in bar graph format.




Graph Mode 航

It indicates the selected sensor data in graph format.



User Group


You can use the User Group function via $\overline{\Xi \Box}$ button on top left corner of screen.




1. After entering User Group function, select sensor data items to be grouped.



2. Once item selection is completed, create a group via 'Add a New Group'.



3. Group creation is completed.



Ŭ	同	You can delete a created group.
L.		You can change the group order.

Search

After entering a search word, touch ${f Q}$, and you can search sensor data.



Arrangement, Unit Change

You can arrange items by touching sensor names, and change the unit by touching unit. Touch *A* at top right corner of each title.


	🚳 🚯	Multi Data Analy		E (1	· ••		E Li	Multi Data	Analysis		
				Ę	è ⊕						
					c	EE	Multi Data	Analysis (5)	Time 00:29:0	8 🔳 =	
	System	Sensor Name		alue			System	Sensor Nam		Value	t
I	ENGINE	2 SMARTRA2 Built-in		OFF -			ENGINE	239 Altitude Adaption V	alue	0.000 -	
I	ENGINE	19 Tank Leakage Detection by Pressure System Supported	a.	OFF -			ENGINE	2 SMARTRA2 Built-in		OFF -	
I	ENGINE	239 Altitude Adaption Value	h	3.984 -			ENGINE	19 Tank Leakage Detect Pressure System Support	tion by Under	OFF -	
I	ENGINE	241 Air Mass Flow Maxim	LP	-0.1 Jan	m		ENGINE	241 Air Mass Flow Maxir		0.0 kg	/h
Ī	ENGINE	244 Brake Boost Vacu	`	`\/	/ `	'\	ENC Sort	by Unit			1
		(•	l	6		Unit			e	
			LD.	Ν	2					=	I
		\ \ \	•		-					=	
		\backslash		/	、 、		kg/h			=	I
		\rangle		()			kg/h hPa			=	I
		\rangle		$\left(\right)$	\rangle		-		01		l
		\rangle		$\left(\right)$		$\left\{ \right\}$	-	Close	ок		
		\rangle		$\langle \rangle$		\$	-	Close	ок		
		\rangle		$\langle \rangle$		\$	-	Close	ок		
		\rangle		$\langle \rangle$		{	-	Close	ок		
		\rangle		$\langle \rangle$)	{	-	Close	ок		
		\rangle		$\langle \rangle$)		-	Close	ок		
		>		$\langle \rangle$	>	{	-	Close	ок		
		\rangle		$\langle \rangle$	>		-	Close	ок		
		\rangle		$\langle \rangle$	>	Ś		Close	ок		
		Ģ	+3		>				ок		

Bottom Function Buttons

Selective Display	This only shows the sensor values of the sensor data items, which were selected based on needs. The entire sensor data values are shown when Fixed Output function is turned off.
چ Actuation Test	You can check change in sensor data by forcefully driving the actuator through Control Module.
Clear Data	Select a system to perform forced driving. This initializes the collected sensor data values, and recollects them.
© Stop	This function collects sensor data values over a certain period of time, and stops the sensor data values. 'Start' and 'Stop' buttons operate in turn.
Recorded Data	This function analyzes the saved sensor data file. This is linked to Saved Data Analysis function.

Screen Control

1. You can spread or fold the screen by dragging \ddagger button upwards or downwards.



2. You can maximize/minimize the items in Graph Mode.

